



Timber bollard with continuous mowstrip

1:10

- NOTES:
1. All dimensions in millimetres.
 2. Bollards to be set at consistent intervals, 1.6m maximum centres
 3. Timber treatment:
 - Sawn timber in contact with ground to be H4. Cut ends of timber shall be treated with a timber preservative (Metalex or similar) prior to installation.
 - Treatment shall comply with the current requirements of the Timber Preservation Council. All timber shall be branded with the appropriate woodmark. It is preferred that timber be treated at least 2 months prior to use.
 4. Timber shall be dressed and free of splinters, significant cracks and other large blemishes. Minor knots are acceptable.
 5. Bollards are to be installed true vertical, and in a continuous line with each other, offset consistently from adjacent paths or hard surfaces.
 6. If located on an area with cross slope, ensure concrete collar or mowing strip follows the contour tidily.

These drawings are not suitable for construction and are provided for guidance only. They should be reviewed by a suitably qualified engineer or landscape architect and modified to meet site-specific requirements.



PROJECT:			
0:	Information	PCF	PCF
REV	DESCRIPTION	BY	CHKD

4/11/2025

PROJECT NAME:			
PCF STANDARD DETAILS-BOLLARD			
ISSUED FOR:			
Information			
PROJECT NO.:	SCALE:	SHEET NUMBER:	REVISION:
	1:10	PCF004	0